



## EPBANOUT



### PRODUCT DESCRIPTION:

Eco-friendly fabric composed of a 290-µm polyester, which is coated with a printable layer on one side. For solvent, eco-solvent, latex and UV inkjet printing. EPBANOUT is intended for outdoor application. Matt surface finish.

### FILM FEATURES:

• Total thickness	(Indicative value) <b>290 µm</b>	
• Total weight	(Indicative value) <b>230 g/m<sup>2</sup></b>	
• Translucency	(Indicative value) <b>20</b>	
• Yarn/weft tear resistance	(Average values) <b>20 daN   25 daN</b>	Method <b>DIN 53.363</b>

### PRINTING GUIDE:

- Printable only on one side (outer side).
- Touch-dry after less than 5 minutes depending on printer used.
- Optimal drying time for the inks before laminating or further processing is 24 hours minimum.

### USER'S INSTRUCTIONS:

- Operating temperature range: +10 °C to +30 °C (+50 °F to +86 °F)
- Relative humidity during application: with relative humidity between 30 and 70 %
- Temperature resistance of the banner: -30 °C to +70 °C (-22 °F to +158 °F)

### STORAGE:

- |   |   |
|---|---|
| Storage period before use<br><b>1 year</b>                                | Storage area<br><b>in a dust-free environment</b>             |
| Storage temperature<br><b>+15 °C to +25 °C (+59 °F to +77 °F)</b>         | Storage method before use<br><b>in its original packaging</b> |
| Relative humidity during storage<br><b>with relative humidity of 50 %</b> | Orientation of rolls before use<br><b>vertically</b>          |

### NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).