



FM580

PRODUCT DESCRIPTION:

500- μ m, magnetic film, which is coated with an acrylic adhesive; with a pole width of 2 mm. To be used in combination with the printable ferrous VF180WM film. For indoor use.

FILM FEATURES:

- Thickness (Indicative value)
500 μ m
- Total thickness (Indicative value)
700 μ m
- Total weight (Indicative value)
1950 g/m²
- Magnetic force (Indicative value)
 ≥ 24 g/cm²

LINER:

- Silicone-coated paper.

ADHESIVE PROPERTIES:

after 20 minutes of application (Indicative value)
8 N/25 mm

ADHESIVE:

- Acrylic adhesive.

USER'S INSTRUCTIONS:

- Between +10 °C and +50 °C (+50 °F and +122 °F).
- Operating temperature range: -5 °C to +40 °C (+23 °F to +104 °F) with relative humidity between 10 % and 80 %.
- Intended for indoor application.
- The film can be cut using a cutter or scissors.
- In the case of an already painted substrate, apply to undamaged original paintwork only. If the paintwork is not original and/or damaged, the application and the removal are at the judgement and risk of the installer.

STORAGE:

- Storage period before use
1 year
- Storage temperature
+20 °C (+68 °F)
- Relative humidity during storage
with relative humidity between 10 % and 80 %
- Storage area
in a dust-free environment and protected from direct sun exposure
- Storage method before use
in its original packaging
- Orientation of rolls before use
vertically

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods, which are available on request. Please feel free to contact us to get the latest instructions in use. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.