



FRONT4V4



PRODUCT DESCRIPTION:

A 370-µm, hot-laminated banner, composed of polyester and PVC. Designed for standard solvent, eco-solvent, latex and UV inkjet printing. FRONT4v4 is intended for use as an advertising/event banner. Printable on the inner side. Satin surface finish.

FILM FEATURES:

• Total thickness	(Indicative value) 370 µm	
• Total weight	(Indicative value) 440 g/m²	
• Yarn/weft thread	(Indicative value) 1000 x 1000 (DTex)	
• Yarn/weft tear resistance	(Average values) 90 N 85 N	Method ISO 13937-2 : 2000

PRINTING GUIDE:

- Printable on the inner side.
- Printing temperature range: between +18 °C and +25 °C (+64 °F and +77 °F).
- Touch-dry after less than 5 minutes depending on printer used.
- For any application, optimal drying time for the inks is 24 hours minimum.

USER'S INSTRUCTIONS:

- The FRONT4v4 banner is specially intended for use as a tautly stretched advertising/event banner. Repeated folding or creasing may provoke premature damage to the banner.

STORAGE:

- | | |
|---|---|
| Storage period before use
1 year | Relative humidity during storage
with relative humidity between 40 % and 60 % |
| Storage temperature
+18 °C to +25 °C (+64 °F to +77 °F) | Storage method before use
in its unopened original packaging |

DURABILITY: (Central European climate)

- Vertical outdoor exposure, unprinted: 1 year.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.