



## FRONTOPAC



### PRODUCT DESCRIPTION:

PVC-coated polyester banner of 680 g/m<sup>2</sup>, suitable for standard solvent, eco-solvent, latex and UV inkjet printing. Satin surface finish, inkjet varnish on both sides for double-sided printing.

### FILM FEATURES:

• Total thickness	(Indicative value) <b>490 µm</b>	
• Total weight	(Indicative value) <b>680 g/m<sup>2</sup></b>	
• Opacity	(Indicative value) <b>100 %</b>	
• Yarn/weft thread	(Average values) <b>550 x 550 (DTex)</b>	Method <b>DIN EN ISO 2286-2</b>
• Yarn/weft tear resistance	(Average values) <b>200 N   200 N</b>	Method <b>DIN 53363</b>

### PRINTING GUIDE:

- Printable on both sides.
- Touch-dry after less than 5 minutes depending on printer used.
- Optimal drying time for the inks before laminating or further processing is 24 hours minimum.

### USER'S INSTRUCTIONS:

- Temperature resistance of the banner: -30 °C to +70 °C (-22 °F to +158 °F)
- Anti-curl properties: prevents the canvas from curling up over time.
- Banner assembly is possible by using Neoprene® glue (1) or double-sided adhesive tape such as STRONGBAN3.

### STORAGE:

- |   |   |
|---|---|
| Storage period before use<br><b>1 year</b>                                | Storage area<br><b>in a dust-free environment</b>             |
| Storage temperature<br><b>+15 °C to +25 °C (+59 °F to +77 °F)</b>         | Storage method before use<br><b>in its original packaging</b> |
| Relative humidity during storage<br><b>with relative humidity of 50 %</b> | Orientation of rolls before use<br><b>vertically</b>          |

### NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).

(1) Neoprene® is a registered trademark of E.I. du Pont de Nemours and Company.