



# HEX 100 HIGH TACK



## PRODUCT DESCRIPTION:

110-µm, stabilised paper, which is coated with a pressure-sensitive, rubber adhesive. Intended for creating and applying kits (logos, cut-out letters of ideally less than 5 cm (1.97 in.) etc.).

## FILM FEATURES:

- Thickness (Indicative value)  
**110 µm**
- Tensile strength (Indicative value)  
**92 N/25 mm**
- Elongation at break (Indicative value)  
**14 %**

## ADHESIVE PROPERTIES:

- Measurement support steel (Indicative value)  
Film's adhesion **2 N/25 mm**

## ADHESIVE:

- Natural rubber-based adhesive.

## USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +15 °C (+59 °F)
- Operating temperature range: +15 °C to +35 °C (+59 °F to +95 °F)
- This tape is suitable for applications requiring good stability over time (relative to dimensional stability and long-term storage) and moisture resistance.
- Good adhesion to the liner: reducing wrinkling, tunnelling and edge curling.

## STORAGE:



Storage period before use  
**1 year**



Storage temperature  
**+21 °C (+70 °F)**



Relative humidity during storage  
**with relative humidity of 50 %**



Storage method before use  
**in its unopened original packaging**

## NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).