



HEX 750

PRODUCT DESCRIPTION:

A 100-µm, transparent film, which is coated with a pressure-sensitive acrylic adhesive.

FILM FEATURES:

- Film thickness (Average values) **100 µm**
- Total thickness (film + adhesive) (Average values) **120 µm**

LINER:

- Silicone-coated paper 60 g/m².

ADHESIVE PROPERTIES:

- Peel strength test at 180°; Measurement support glass (Average values) Method **HEXFTM001**
after 20 minutes of application **1 N/25 mm**

ADHESIVE:

- Acrylic adhesive.

USER'S INSTRUCTIONS:

- This tape is especially suitable for:
- For transferring the S5CANB carbon effect film and the fluorescent films of the F610 series. Dry application method.
- For transferring the printable flex films BLOCKPRINT and NYLPRINT.
- For more information on the application method of the HEX750 tape with textile films, please refer to the PRINTFLEX Application Guide on the «Professionals» pages, category «Films for textile» on the site www.hexis-graphics.com.

STORAGE:

- Storage period before use **1 year**
- Storage temperature **+15 °C to +25 °C (+59 °F to +77 °F)**
- Relative humidity during storage **with relative humidity of 50 %**
- Storage area **in a dust-free environment**
- Storage method before use **in its unopened original packaging**
- Orientation of rolls before use **vertically**

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.