



HEX 905 HIGH TACK 110 ?m

PRODUCT DESCRIPTION:

A 110-µm embossed PP film, which is coated with a pressure-sensitive acrylic adhesive.

FILM FEATURES:

- Thickness (Average values)
110 µm

ADHESIVE PROPERTIES:

- Film's adhesion (Average values)
1,1 N/cm
- Resistance to solvents: the adhesive is resistant to most chemicals (alcohol, petrol, diluted acids, oils, fuels).

ADHESIVE:

- Acrylic adhesive.
- Immediate adhesion, suitable for wet application.

USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +10 °C (+50 °F)
- Operating temperature range: +15 °C to +35 °C (+59 °F to +95 °F)
- For best results, the letter transferring process should preferably be carried out on the same day that the transfer film has been applied to the letters.

STORAGE:

-  Storage period before use
6 months
-  Storage temperature
+15 °C to +25 °C (+59 °F to +77 °F)
-  Relative humidity during storage
with relative humidity between 30 % and 70 %
-  Storage method before use
in its unopened original packaging

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.