



HEX 910 MEDIUM TACK



PRODUCT DESCRIPTION:

98-µm polypropylene film, which is coated with a pressure-sensitive, rubber adhesive. Intended for creating and applying kits.

FILM FEATURES:

- Thickness (Indicative value)
98 µm
- Tensile strength (Indicative value)
105 N/25 mm
- Elongation at break (Indicative value)
> 100 %

ADHESIVE PROPERTIES:

- Measurement support steel (Indicative value)
2 N/25 mm

ADHESIVE:

- Natural rubber-based adhesive.
- Immediate adhesion.

USER'S INSTRUCTIONS:

- Recommended minimum application temperature: +15 °C (+59 °F)
- Operating temperature range: +15 °C to +35 °C (+59 °F to +95 °F)
- Resistant to humidity for long-term storage.
- Thanks to a good dimensional stability, the HEX910 tape is resistant to stretching and folding during application.

STORAGE:



Storage period before use
1 year



Storage method before use
in its unopened original packaging



Storage temperature
+21 °C (+70 °F)

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.