



HEX 930 MEDIUM TACK



PRODUCT DESCRIPTION:

A 100-µm, transparent PP film, which is coated with a pressure-sensitive rubber adhesive. Intended for creating and applying kits (logos, cut letters ideally between 5 cm and 31 cm (1.97 in. and 12.20 in.) etc.).

FILM FEATURES:

- Total thickness (film + adhesive) (Indicative value)
100 µm
- Tensile strength (Indicative value)
66 N/25 mm
- Elongation at break (Indicative value)
> 100 %

ADHESIVE PROPERTIES:

- Peel strength test at 90°; Measurement support steel (Indicative value)
1,9 N/25 mm
- Film's adhesion

ADHESIVE:

- Natural rubber latex adhesive.

USER'S INSTRUCTIONS:

- Dry application method
- Recommended minimum application temperature: +15 °C (+59 °F)
- Operating temperature range: +15 °C to +35 °C (+59 °F to +95 °F)
- Tape for use with high-precision applications, superimposed applications, and applications of coloured films whether they are calendered or cast.
- Good adhesion to the liner, high transparency and reduced tunnelling.

STORAGE:

- Storage period before use
6 months
- Storage temperature
+15 °C to +25 °C (+59 °F to +77 °F)

- Relative humidity during storage
with relative humidity between 30 % and 70 %
- Storage method before use
in its unopened original packaging

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.