



HEX 960

PRODUCT DESCRIPTION:

Transparent, 100-µm polyester film, which is coated with a pressure-sensitive, acrylic adhesive.

FILM FEATURES:

- Film thickness (Indicative value)
100 µm

LINER:

- Silicone-coated paper 87 g/m² with grey HEXIS print.
- Stable under hygrometric variations

ADHESIVE PROPERTIES:

(Measured average values at publication of the technical data sheet)

- Peel strength test at 180°; Measurement support glass (Average values) Method
after 24 hours of application **2 N/25 mm** **HEXFTM001**

ADHESIVE:

- Acrylic adhesive.

USER'S INSTRUCTIONS:

- This tape is used for transferring the UFLEX7PV2, SILKPRINT or NYLPRINT flex films for digital printing.
- After transferring, remove the HEX 960 tape while it is still hot, right after pressing the textile. The adhesion of the HEX 960 tape increases as the temperature decreases; a cold removal would therefore be more difficult, even impossible.
- For more information on the application method, please refer to the PRINTFLEX Application Guide under the «Professionals» heading, in the «Films for textile» category on our website >www.hexis-graphics.com.

STORAGE:

- | | |
|--|---|
| <ul style="list-style-type: none"> Storage period before use
1 year Storage temperature
+15 °C to +25 °C (+59 °F to +77 °F) Relative humidity during storage
with relative humidity of 50 % | <ul style="list-style-type: none"> Storage area
in a dust-free environment Storage method before use
in its unopened original packaging Orientation of rolls before use
vertically |
|--|---|

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.