



# POD225SOLV



## PRODUCT DESCRIPTION:

220-µm white translucent polyester film. For solvent, eco-solvent, latex and UV inkjet printing. For application to lightboxes. Satin surface finish.

## FILM FEATURES:

- Total thickness (Indicative value)  
**220 µm**
- Total weight (Indicative value)  
**290 g/m<sup>2</sup>**

## PRINTING GUIDE:

- The printable side is the satin one (outer side).
- Printing temperature range: +15 °C to +30 °C (+59 °F to +86 °F) with relative humidity between 30 % and 60 %.
- Touch-dry after less than 10 minutes depending on printer used.
- Optimal drying time for the inks before laminating, coating or further processing is 24 hours.

## OPERATING RECOMMENDATIONS:

- The surface finish of your printings may be modified/improved/protected by applying the appropriate V700 (matt, satin or glossy) laminate.

## STORAGE:



Storage period before use  
**1 year**



Storage temperature  
**+15 °C to +25 °C (+59 °F to +77 °F)**



Relative humidity during storage  
**with relative humidity between 40 % and 60 %**



Storage method before use  
**in its unopened original packaging**

## NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the absolute suitability of the medium for each specific application. All of the published information is based on measurements regularly performed in the laboratory. All the published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).