



POPPRIMO



PRODUCT DESCRIPTION:

Multilayer film composed of a 220-µm white/white opaque PVC and boPET. For solvent, eco-solvent, latex and UV inkjet printing. Matt white surface finish.

FILM FEATURES:

- Total thickness (Indicative value)
220 µm
- Total weight (Indicative value)
290 g/m²

PRINTING GUIDE:

- Printing on the grain side (outer side of the roll).
- Printing temperature range: +15 °C to +30 °C (+59 °F to +86 °F) with relative humidity between 30 % and 60 %.
- Touch-dry after less than 10 minutes depending on printer used.

USER'S INSTRUCTIONS:

- Suitable for roll-up and wall displays.

OPERATING RECOMMENDATIONS:

- Optimal drying time for the inks before laminating or further processing is 24 hours minimum.
- The surface finish of your printings may be modified/improved by applying the appropriate laminate: V650, V700, V750 or PSPOP. DO NOT USE heat-sealing (heat encapsulating) film.

STORAGE:

- Storage period before use
2 years
- Storage temperature
+12 °C to +32 °C (+54 °F to +90 °F)
- Relative humidity during storage
with relative humidity between 45 % and 65 %
- Storage area
in a dust-free environment
- Storage method before use
in its unopened original packaging
- Orientation of rolls before use
vertically

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the absolute suitability of the medium for each specific application. All of the published information is based on measurements regularly performed in the laboratory. All the published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.