

## TEXWALLV2



### PRODUCT DESCRIPTION:

240-µm, white mural textile, which is composed of a woven polyester fabric and coated with a printable layer on one side and a pressure-sensitive, removable, rubber-based adhesive on the other side. Designed for solvent, eco-solvent, latex and UV printing. Ease of application and removal without leaving any adhesive residues. Satin surface finish.

### FILM FEATURES:

- Thickness (Indicative value)  
**240 µm**
- Weight (Indicative value)  
**230 g/m<sup>2</sup>**
- Total weight (Indicative value)  
**340 g/m<sup>2</sup>**

### LINER:

- Silicone-coated paper 80 g/m<sup>2</sup>.

### ADHESIVE PROPERTIES:

- Peel strength test at 180°; Measurement support glass
 

|                                 |                  |             |
|---------------------------------|------------------|-------------|
|                                 | (Average values) | Method      |
| after 20 minutes of application | <b>1 N/25 mm</b> | <b>FTM1</b> |
|                                 | (Average values) | Method      |
| after 24 hours of application   | <b>1 N/25 mm</b> | <b>FTM1</b> |

### ADHESIVE:

- Synthetic rubber adhesive.
- Immediate adhesion; removable adhesive.

### PRINTING GUIDE:

- Maximum heating temperature during printing: +80 °C (+50 °F).
- Touch-dry after less than 10 minutes depending on printer used.
- Optimal drying time for the inks before laminating or further processing is 24 hours minimum.

### USER'S INSTRUCTIONS:

- Operating temperature range: +10 °C to +50 °C (+50 °F to +122 °F)
  - Medium-term indoor wall application.
  - Adhesion to aluminium, Dibond®, smooth sheet metal.

*For applications to any other substrate or painted and/or rough surfaces, run a test to check the compatibility between the film and the substrate before applying the TEXWALLV2 film. Any application of film to a non-recommended substrate is at the judgement and risk of the installer.*

- Application of the lengths by overlapping.

*A wallpaper cut may be carried out in order to obtain an edge-to-edge finish.*

- The film can be applied to flat or irregular surfaces as well as angles without the formation of any bubbles or folds.

### STORAGE:



Storage period before use  
**2 years**




Storage temperature  
**+15 °C to +25 °C (+59 °F to +77 °F)**



Relative humidity during storage  
**with relative humidity of 50 %**



Storage method before use  
**in its unopened original packaging**



## DURABILITY:

- Vertical indoor exposure on flat surfaces:
  - Unprinted: 3 years.
  - Without significant traces of adhesive left after removal: 3 months.

## NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All of the published information is based on measurements regularly performed in the laboratory. The published information does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).