



## TECHNICAL DATA SHEET - TRANSPARENT FLEXIBLE FILM PETSAFE

Film composed of a 50- $\mu\text{m}$ , ultra-transparent extruded PET. Intended to create a physical barrier between people preventing direct spread by droplet transmission.

### **FILM FEATURES:**

	<u>Indicative value</u>
• Thickness ( $\mu\text{m}$ ):	$50 \pm 10\%$
• Surface coat weight ( $\text{g}/\text{m}^2$ ):	$70 \pm 10\%$
• Transparency (400-700 nm visible):	$> 90 \%$
• Gloss (G.U.):	$> 99$

### **USER'S INSTRUCTIONS:**

- To be fastened on a frame using adhesive (e.g. cyanoacrylate, chloroprene, etc.), double-sided adhesive tape and/or staples, etc.
- Can be cleaned with hydroalcoholic solutions or other usual detergents.
- Using abrasive sponges may scratch the film.

### **STORAGE:**

- Shelf life:

The shelf life of this film is 2 years when stored upright in its original packaging in a dust-free environment at a temperature ranging from  $+15 \text{ }^\circ\text{C}$  and  $+25 \text{ }^\circ\text{C}$  ( $+59 \text{ }^\circ\text{F}$  to  $+77 \text{ }^\circ\text{F}$ ) with relative humidity of 50 %.

### **DURABILITY:**

- For short-term use.

### **NOTES:**

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application.

The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website [www.hexis-graphics.com](http://www.hexis-graphics.com).