



TECHNICAL DATA SHEET - PLOTTER VINYLs - POLYPROPYLENE TAPE HEX 910 MEDIUM TACK

98- μ m polypropylene film, which is coated with a pressure-sensitive, rubber adhesive. Intended for creating and applying kits.

FILM FEATURES:

Indicative values

- | | |
|-------------------------------|-------|
| • Thickness (μ m): | 98 |
| • Tensile strength (N/25 mm): | 105 |
| • Elongation at break (%): | > 100 |

ADHESIVE PROPERTIES:

Indicative value

- | | |
|--------------------------------|---|
| • Adhesion to steel (N/25 mm): | 2 |
|--------------------------------|---|

ADHESIVE:

- Natural rubber based.
- Immediate adhesion.

USER'S INSTRUCTIONS:

- Minimum recommended application temperature: +15 °C (+59 °F).
- Range of operating temperatures: +15 °C to +35 °C (+59 °F to 95 °F).
- Resistant to humidity for long-term storage.
- Thanks to a good dimensional stability, the HEX910 tape is resistant to stretching and folding during application.

STORAGE:

- Shelf life (before application):

The shelf life of this film is 1 year when stored unopened in its original packaging at a temperature of +21 °C (+70 °F) with relative humidity of 50 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.