



TECHNICAL DATA SHEET - PLOTTER VINYL SILICONE-COATED PAPER

Silicone-coated Kraft paper 137 g/m², stable under hygrometric variations. Protective liner.

PAPER FEATURES:

| | <u>Indicative values</u> | |
|-------------------------------|--------------------------|-----------------|
| • Thickness (µm): | 140 | |
| • Paper moisture (% RH): | 4.5 | |
| | <u>Average values</u> | <u>Standard</u> |
| • Weight (g/m ²): | 137 | HEXGSM001 |
| • Release (N/25 mm): | 1.05 | HEXFTM003 |

USER'S INSTRUCTIONS:

- Operating temperature range: +10 °C to +30 °C (+50 °F to +86 °F) with relative humidity between 30 and 70 %.
- Stable under hygrometric variations.

STORAGE:

- Shelf life (before opening the original packaging):
1 year when stored unopened in its original packaging at a temperature ranging from +15 °C and +25 °C (+59 °F to +77 °F) with relative humidity of 50 %.

NOTES:

Due to the great variety of substrates and the growing number of new applications, the installer must check the suitability of the medium for each application. The measuring methods for the standards quoted above served as the basis for the development of our own measuring methods which are available on request. Please feel free to contact us to get the latest instructions in use.

All the published information is based on measurements regularly performed in the laboratory. It does not however constitute a binding guarantee. The seller cannot be held liable for indirectly related damages and assumes no liability for claims that are higher than the replacement value of the purchased product. All specifications are subject to potential changes without prior notice. Our specifications are automatically updated on our website www.hexis-graphics.com.